



4-5K

## SOLARATOR SERIES

Works with a Wide Range of Batteries: Experience Uninterrupted Power, Even in Areas with Grid Instability

### S6-EO1P(4-5)K-48-EU

Single Phase | Low Voltage



- Compatible with generator as backup power supply for off grid system
- Easily expand system capacity using parallel connections and AC coupling
- 10 seconds of 200% overload capability
- Multiple battery options including fast configuration for non-communicating batteries
- Support one click fast charging mode
- Supports dual backup load for intelligent load prioritizing

UK

t: +44 113 328 0870 (sales)  
+44 1514 536515 (service)

e: [europesales@solisinverters.com](mailto:europesales@solisinverters.com)  
[ukservice@solisinverters.com](mailto:ukservice@solisinverters.com)

w: [solisinverters.com/uk](http://solisinverters.com/uk)



## DATASHEET

Models	4K	5K
<b>Solar Charger</b>		
Max. usable PV input power	5.5 kW	6.5 kW
Max. input voltage		500 V
Rated voltage		360 V
Start-up voltage		90 V
MPPT voltage range		90 - 430 V
Max. input current		16 A / 16 A
Max. short circuit current		40 A
Max. solar charge current		100 A
MPPT number / Max. input strings number		1 / 2
<b>Battery</b>		
Battery type		Li-ion / Lead-acid
Rated battery voltage		40 - 60 V
Max. charge / discharge power		5 kW / 5 kW
Max. charge / discharge current		100 A
Communication		CAN
<b>Inverter Output</b>		
Rated output power	4 kVA / 4 kW	5 kVA / 5 kW
Operation phase		L/N/PE
Rated grid voltage		230 V ± 1%
Rated grid frequency		50 Hz / 60 Hz ± 0.1%
Surge capacity	8 kVA	10 kVA
Max. output current	20 A	25 A
Output voltage waveform		Pure sine wave
Transfer time		10 ms typical, 20 ms Max
THDv (@linear load)		< 3%
Peak efficiency (PV-AC)		96.6%
<b>AC Charger (grid port and generator port)</b>		
Max. input power	6 kW	7 kW
Rated input voltage		L/N/PE, AC 230 V
Selectable voltage range		90 - 280 V
AC frequency range		50 Hz / 60 Hz
Max. input current	26 A	30 A
Max. AC charge current	60 A	80 A
<b>Protection</b>		
Output over voltage protection		Yes
Output over current protection		Yes
Short circuit protection		Yes
Surge protection		Yes
Temperature protection		Yes
Integrated AFCI 2.0		Optional
<b>General Data</b>		
Dimensions (W × H × D)		340 × 495 × 170 mm
Weight		14.1 kg
Topology		High frequency non-isolation
Relative humidity		5% - 95% (Non-condensing)
Operating ambient temperature range		-10 ~ +60°C
Storage temperature range		-25 ~ +60°C
Ingress protection		IP21
Max. operation altitude		2000 m
Parallel capability		6 units
Safety standard		IEC 62109, IEC 61000, 55011
<b>Features</b>		
DC connection		Terminal connectors
AC connection		Terminal connectors
Display		LCD
Communication		CAN, BMS, Dry-contact, Bluetooth, Optional: Wi-Fi