

Introducing Strom Single Phase Instantaneous Water Heaters



IDEAL FOR SHOWER & MULTI BASINS

Strom Single Phase Water Heaters are perfect for domestic applications, ranging from small point of use to larger multipoint systems and hot water showers. The Single Phase Instantaneous really can do it all.

Single Phase Instantaneous Water Heater Specification.

This elite water heater is the crown jewel in the product range, introducing the Single Phase Instantaneous Water Heater.

This compact and neat wall mounted and recessed heater can output to multiple outlets in a property making it the perfect replacement for hot water cylinders and gas boilers in smaller dwellings or to supplement requirements in larger applications. Providing unlimited hot water with astounding flow rates this product really is versatile with an exceptional range of uses.

- Unique Matte IMD Splash Proof Front Cover.
- Utilises patented enclosed loop heating system.
- Multi-Layer heating chamber reducing lime-scale buildup.
- Directly set and maintain output temperature automatically.
- Large widescreen LED Display with Touch controls.
- Displays output temperature and target temperature.
- Audible feedback for button presses.
- Automatic fault detection with on screen feedback.



Technical Specification:

Product Code	SEIH7KTS2	SEIH9KTS2	SEIH11KTS2	SEIH14KTS2
Body Material	Matte ABS	Matte ABS	Matte ABS	Matte ABS
Voltage	230VAC	230VAC	230VAC	230VAC
Power	7.0kW	9.0kW	11.0kW	13.5kW
Rated Current	32A	40A	48A	62A
Cable Size (Minimum)	4mm	6mm	10mm	10mm
Breaker Size (Minimum)	40A	45A	50A	63A
Max Working Pressure	6 Bar	6 Bar	6 Bar	6 Bar
Minimum Inlet Pressure	0.2 Bar	0.2 Bar	0.2 Bar	0.2 Bar
Max Recommended Flowrate	4LPM	5LPM	6LPM	7LPM
Temperature Cut-Out	67°C	67°C	67°C	67°C
Control Method	Touch Screen	Touch Screen	Touch Screen	Touch Screen
Water Connections	1/2" BSP Male	1/2" BSP Male	1/2" BSP Male	1/2" BSP Male
Dimensions (HxWxD)	358x246x85mm	358x246x85mm	358x246x85mm	358x246x85mm
ERP Rating	A	A	A	A

Introducing Strom Three Phase Instantaneous Water Heaters



IDEAL FOR COMMERCIAL APPLICATIONS

The Strom Three Phase Instantaneous Water Heater requires a three phase connection, but when you feed this beast right you will be rewarded with incredible flow rates and an unlimited hot water supply for your application.

Three Phase Instantaneous Water Heater Specification.

When your demand is uncompromising and flow rates are a priority the Strom 3 Phase Commercial Water Heaters have you covered.

This compact and neat wall mounted and recessed heater can output to multiple outlets in a commercial property making it the perfect replacement for hot water cylinders and gas boilers in larger & public buildings. Providing unlimited hot water with astounding flow rates this product really is versatile with an exceptional range of uses.

- Unique Matte IMD Splash Proof Front Cover.
- Utilises patented enclosed loop heating system.
- Multi-Layer heating chamber reducing lime-scale buildup.
- Directly set and maintain output temperature automatically.
- Large widescreen LED Display with Touch controls.
- Displays output temperature and target temperature.
- Audible feedback for button presses.
- Automatic fault detection with on screen feedback.



Technical Specification:

Product Code	SEIH18KTS2	SEIH21KTS2	SEIH24KTS2
Body Material	High Strength Matte ABS	High Strength Matte ABS	High Strength Matte ABS
Voltage	415VAC	415VAC	415VAC
Power	18kW	21kW	24kW
Rated Current	27A	32A	36A
Cable Size (Minimum)	4mm	6mm	6mm
Breaker Size (Minimum)	32A	40A	40A
Max Working Pressure	6 Bar	6 Bar	6 Bar
Minimum Inlet Pressure	0.2 Bar	0.2 Bar	0.2 Bar
Max Recommended Flowrate	9LPM	10LPM	12LPM
Temperature Cut-Out	67°C	67°C	67°C
Control Method	Touch Screen	Touch Screen	Touch Screen
Water Connections	3/4" BSP Male	3/4" BSP Male	3/4" BSP Male
Dimensions (HxWxD) (mm)	488x282x102mm	488x282x102mm	488x282x102mm
ERP Rating	A	A	A